




KONICA MINOLTA

Spectrophotometer **CM-5**

Stand alone Top-Port Spectrophotometer
with maximum Flexibility and Versatility



Food & Ingredients



Pharmaceuticals & Chemicals



Cosmetics & Perfumes



The essentials of imaging

CM-5 Top-Port Spectrophotometer

offering versatile usage

and simple operation

Requirements for Colour measurement of Foods, Ingredients, Flavours & Fragrances, Drinks, Pharmaceuticals, Cosmetics and base Chemicals are especially demanding due to the extreme diversity of sample forms, from solids to powders, granules paste, liquid to opaque, translucent or transparent, all forms are found.

An instrument capable of covering this wide range of products must not only be flexible in terms of measurement methodology but even more importantly in terms of user friendliness and minimum sample preparation time to allow fast routine measurements in the laboratory or in production control.

The new Konica Minolta Bench-Top Spectrophotometer CM-5 offers exactly this combination of versatility and simplicity to cover all the requirements in a true "All in one" concept.

Full-featured


Stand alone instrument that

covers all your applications

➔ The top-port concept allows easy sample positioning and measurement of solid samples. Just place the sample on the measuring port and press the measurement button.

Measuring areas with 30, 8 and 3 mm allow perfect adaption to the sample size.

Samples in paste, powder or granule form can easily be measured with the optional Petri-Dish set.



Reflection measurement of solids




Reflection measurement of paste products

➔ Simply sliding the top cover, opens the large transmission chamber to measure all kind of transparent liquids or solids, such as foils or glass plates in Transmission mode.

For liquids, glass or plastic cells of up to 60 mm path can be used, including 12.5 mm standard glass cells when using the optional adapter.



Measurement of liquids in transmission




Measurement of solids in transmission



Functions & Features that make your daily work faster and easier


- ➔ The large LCD screen show the measurement results delete either numerically or graphically including Reflectance values, all colour systems and PASS/FAIL evaluations.
- ➔ To simplify the operation; the “Operation Wizard” is a perfect step by step on screen user guide in 7 Languages to ease operation.
- ➔ To simplify the use of the CM-5 by several people in parallel, measurement data and instrument settings can be saved on a USB stick.
- ➔ In addition to the classic colorimetric evaluation systems, the CM-5 offers measurement results of liquids to be evaluated in terms of industry specific indices (colour scales) such as Gardner, Iodine, Hazen (APHA), European and US Pharmacopeia.



! Top 10 Features

1. High-end Spectrophotometer with wide wavelength range
2. Top-port concept for Reflectance measurements
3. Large Transmission chamber for liquids & solids
4. Stand alone function with LCD Screen and Firmware
5. Measurement of Industry specific indices
6. Storage of user settings and data on USB stick
7. “Operation Wizard” with real time on screen user guidance
8. Firmware in 7 Languages
9. Extremely easy operation with automatic calibration
10. Compact, lightweight and functional Design

Specifications		Spectrophotometer CM-5	
Illumination/viewing system	Reflectance:	di:8°, de:8° (diffuse illumination: 8° viewing) / SCI (specular component included)/SCE (specular component excluded) switchable Conforms to CIE No. 15, ISO 7724/1, ASTM E 1164, DIN 5033 Teil 7, and JIS Z 8722 (Condition c)	
	Transmittance:	di:0°, de:0° (diffuse illumination: 0° viewing)	
Integrating sphere size	Ø152 mm		
Detector	Dual 40-element silicon photodiode arrays		
Spectral separation device	Planar diffraction grating		
Wavelength range	360 nm to 740 nm		
Wavelength pitch	10 nm		
Half bandwidth	Approx. 10 nm		
Measurement range	0 to 175 % (Reflectance or transmittance); Output/display resolution: 0.01%		
Light source	Pulsed Xenon lamp		
Measurement time	Approx. 1 s (to data display/output); Minimum measurement interval: Approx. 3 s		
Measurement/ illumination area	Reflectance:	Changeable by changing mask and settings. LAV: Ø30 mm / Ø36 mm; MAV (optional): Ø8 mm / Ø11 mm; SAV (optional): Ø3 mm / Ø6 mm	
	Transmittance:	Ø20 mm	
Repeatability	Spectral reflectance: Standard deviation within 0.1% (400 nm to 740 nm) / Chromaticity value: Standard deviation within ΔE^*ab 0.04 * When a white calibration plate is measured 30 times at 10-second intervals after white calibration		
Inter-instrument agreement	Within ΔE^*ab 0.15 (Typical) (Based on 12 BCRA Series II color tiles compared to values measured with a master body at 23°C)		
Transmittance chamber	No sides (unlimited sample length); Depth (maximum sample thickness): 60 mm Sample holder (optional) for holding sheet samples or containers of liquid samples can be installed/removed		
Display	14.5 cm TFT color LCD		
Display languages	English, Japanese, German, French, Italian, Spanish, Simplified Chinese		
White calibration	Automatic white calibration (reflectance) / 100% calibration (transmittance) using internal white calibration plate		
Interfaces	USB 1.1 (Connection to PC; USB memory stick); RS-232C standard (Connection to serial printer)		
Observer	2° Standard Observer or 10° Standard Observer		
Illuminant	A, C, D50, D65, F2, F6, F7, F8, F10, F11, F12, ID50, ID65 (simultaneous evaluation with two light sources possible)		
Displayed data	Spectral values, spectral graph, colorimetric values, color-difference values, color-difference graph, pass/fail judgment, pseudo color, color assessment		
Color space	L*a*b*, L*C*h, Hunter Lab, Yxy, XYZ, Munsell, and color differences in these spaces (except for Munsell)		
Index	Reflectance:	M; WI (ASTM E 313-73, ASTM E 313-96); YI (ASTM E 313-73, ASTM E 313-96, ASTM D 1925); ISO Brightness, B (ASTM E 313-73)	
	Transmittance:	Gardner, Iodine, Hazen (APHA), European Pharmacopoeia, US Pharmacopoeia	
User index	User-defined index		
Color-difference equation	ΔE^*ab (CIE 1976), ΔE^*94 (CIE 1994), ΔE_{00} (CIE 2000), ΔE (Hunter), CMC (l: c)		
Pass/fail judgment	Tolerances can be set to colorimetric values (except Munsell), color-difference values, or reflectance index values		
Storable data	Sample data: 4,000 measurements; Target color data: 1,000 measurements		
USB memory stick storage	Storage of measurement data and target color data. Storage/reading of measurement condition settings (Security-en-abled USB memory sticks cannot be used.)		
Power	AC 100 to 240 V, 50/60 Hz (using exclusive AC adapter)		
Size	Slide cover closed: 385 (W) × 192 (H) × 261 (D) mm Slide cover open: 475 (W) × 192 (H) × 261 (D) mm		
Weight	Approx. 5.8 kg		
Operating temperature/humidity range	13 to 33°C, relative humidity 80 % or less (at 35°C) with no condensation		
Storage temperature/humidity range	0 to 40°C, relative humidity 80 % or less (at 35°C) with no condensation		



Konica Minolta Sensing, Inc.
Konica Minolta Sensing Americas, Inc.

Osaka, Japan
New Jersey, U.S.A.

Konica Minolta Sensing Europe B.V.

European Headquarter/BENELUX
German Office
French Office
UK Office
Italian Office
Swiss Office
Nordic Office
Austrian Office
Polish Office
AQUATEKNICA S.A.
SE Sales Division
SE Beijing Office
SE Guangzhou Office
Singapore
Seoul Office

Distribuidor para España y Portugal
Konica Minolta (CHINA) Investment Ltd.

Konica Minolta Sensing Singapore Pte Ltd.
Konica Minolta Sensing, Inc.

Nieuwegein, Netherland
München, Germany
Roissy CDG, France
Milton Keynes, United Kingdom
Milan, Italy
Dietikon, Switzerland
Västra Frölunda, Sweden
Wien, Austria
Wroclaw, Poland
Valencia, Spain
Shanghai, China
Beijing, China
Guangzhou, China
Seoul, Korea

Phone: 888-473-2656 (in USA),
201-236-4300 (outside USA)
Phone: +31(0)30 248-1193
Phone: +49(0)99 4357 156 0
Phone: +33(0)1 493-82519
Phone: +44(0)1908 540-622
Phone: +39 02 39011.425
Phone: +41(0)43 322-9800
Phone: +46(0)31 7099464
Phone: +43(0)1 87882-430
Phone: +48(0)71 33050-01
Phone: +34 963 30 20 13
Phone: +86-021-5489 0202
Phone: +86-010-8522 1551
Phone: +86-020-3826 4220
Phone: +65 6563-5533
Phone: +82(0)2-523-9726

Fax: +31(0)30 248-1280
Fax: +49(0)99 4357 156 99
Fax: +33(0)1 493-84771
Fax: +44(0)1908 540-629
Fax: +39 02 39011.223
Fax: +41(0)43 322-9809
Fax: +46(0)31 474945
Fax: +43(0)1 87882-431
Fax: +48(0)71 734 52 10
Fax: +34 963 30 03 96
Fax: +86-021-5489 0005
Fax: +86-010-8522 1241
Fax: +86-020-3826 4223
Fax: +65 6560-9721
Fax: +82(0)2-523-9729



Certificate No. YKA 0937 154
Registration Date:
March 3, 1995



Certificate No. JQA-E-80027
Registration Date:
March 12, 1997

